CLAIMS

1. A method for recording message activity in a log, the method comprising the steps of:

receiving a request from an application to put a message, comprising message data, to a queue; and

detecting whether there is a previous occurrence of the message data in the log, and if there is not a previous occurrence writing a log record including the message data, but if there is a previous occurrence writing a log record including a reference for locating the previous occurrence of the message data in the log.

- 2. A method as claimed in claim 1 wherein the request to put a message includes an indication that the message data was put to a message queue or got from a message queue in a previous request from the application.
- 3. A method as claimed in claim 2 wherein the indication is a value which indicates that the message data was involved in the immediately preceding request from the application.
- 4. A method as claimed in claim 2 wherein the indication is a token which uniquely identifies the message data within the scope of the application.

25

30

5

5. A method as claimed in claim 1 further comprising the steps:

receiving a request from the application to get a message, comprising message data, from a queue; and

storing a reference, separate from the log and associated with the application, for locating a previous occurrence of the message data in the log.

- 6. A method as claimed in claim 1 wherein if the detecting step detects that there is not a previous occurrence of the message data in the log it further stores a reference, separate from the log and associated with the message, for subsequently locating the message data in the log.
- 7. A method for detecting the re-use of message data comprising the steps:

receiving a request from an application to put a message, comprising message data, to a queue; and

detecting, based on an indicator included with the request, that the message data was previously put to a message queue or got from a message queue by the application.

8. A method as claimed in claim 7 wherein the indicator is a value which indicates that the message data was

30

5

involved in the immediately preceding request from the application.

- 9. A method as claimed in claim 7 wherein the indicator is a token which uniquely identifies the message data within the scope of the application.
- 10. A computer program product, recorded on a medium, comprising instructions which, when executed on a data processing host, causes said host to carry out a method comprising the steps:

receiving a request from an application to put a message, comprising message data, to a queue; and

detecting whether there is a previous occurrence of the message data in the log, and if there is not a previous occurrence writing a log record including the message data, but if there is a previous occurrence writing a log record including a reference for locating the previous occurrence of the message data in the log.

- 11. A computer program product as claimed in claim 10 wherein the request to put a message includes an indication that the message data was put to a message queue or got from a message queue in a previous request from the application.
- 12. A computer program product as claimed in claim 11 wherein the indication is a value which indicates that

30

5

the message data was involved in the immediately preceding request from the application.

- 13. A computer program product as claimed in claim 11 wherein the indication is a token which uniquely identifies the message data within the scope of the application.
- 14. A computer program product as claimed in claim 10 further comprising the steps:

receiving a request from the application to get a message, comprising message data, from a queue; and

storing a reference, separate from the log and associated with the application, for locating a previous occurrence of the message data in the log.

- 15. A computer program product as claimed in claim 10 wherein if the detecting step detects that there is not a previous occurrence of the message data in the log it further stores a reference, separate from the log and associated with the message, for subsequently locating the message data in the log.
- 16. A computer program product, recorded on a medium, comprising instructions which, when executed on a data processing host, causes said host to carry out a method comprising the steps:

5

receiving a request from an application to put a message, comprising message data, to a queue; and

detecting, based on an indicator included with the request, that the message data was previously put to a message queue or got from a message queue by the application.

- 17. A computer program product as claimed in claim 16 wherein the indicator is a value which indicates that the message data was involved in the immediately preceding request from the application.
- 18. A computer program product as claimed in claim 16 wherein the indicator is a token which uniquely identifies the message data within the scope of the application.
- 19. A data processing apparatus comprising:

a non-volatile memory storage device for storing log records thereon in a log comprising one or more log files;

a volatile memory storage device;

means for receiving a request from an application to put a message, comprising message data, to a queue;

5

means for detecting whether there is a previous occurrence of the message data in the log;

means responsive to failing to detect a previous occurrence of the data in the log for writing a log record including the message data; and

means responsive to detecting a previous occurrence of the data in the log for writing a log record including a reference for locating the previous occurrence of the message data in the log.

- 20. An apparatus as claimed in claim 19 wherein the request to put a message includes an indication that the message data was put to a message queue or got from a message queue in a previous request from the application.
- 21. An apparatus as claimed in claim 20 wherein the indication is a value which indicates that the message data was involved in the immediately preceding request from the application.
- 22. An apparatus as claimed in claim 21 wherein the indication is a token which uniquely identifies the message data within the scope of the application.
- 23. An apparatus as claimed in claim 19 further comprising:

means for receiving a request from the application to get a message from the queue; and

means for storing a reference, separate from the log and associated with the application, for locating a previous occurrence of the message data in the log.

24. An apparatus as claimed in claim 19 further comprising:

means responsive to failing to detect a previous occurrence of the message data in the log for storing a reference, separate from the log and associated with the message, for subsequently locating the message data in the log.

25. A data processing apparatus comprising:

means for receiving a request from an application to put a message, comprising message data, to a queue; and

means for deducing, based on an indicator included with the request, that the message data was previously put to a message queue or got from a message queue by the application.

26. A data processing apparatus as claimed in claim 25 wherein the indicator is a value which indicates that the message data was involved in the immediately preceding request from the application.

30

25

27. A data processing apparatus as claimed in of claim 25 wherein the indicator is a token which uniquely identifies the message data within the scope of the application.